

De la Peña

pinturas de la peña  
fábrica de pinturas**MONOPLAYER MATT ACRYLIC PAINT 5000-P**

High Performance and Durability Acrylic Paint

Page 1 de 2

This paint is suitable for indoor as well as for outdoor decoration with a great whiteness and covering power. Its good opacity permits obtaining monoplayer finishing.

It is formulated with water emulsions, high quality pigments, fungicides agents and inox, which gives it antimould and anticorrosive properties being able to be applied over plate or iron with a previous to work with the primer.

This paint is recommended for places where the protection against mould and antibacterial action is needed such as the food industry factories, etc. It also has water-repellent's properties thanks to the addition of additives of silicone water repellents.

**Features**

Color	White
Finishing	Matt
Specific weight	1,64 gr./cc.
Viscosity on having tipped	115 K.U. to 25 °C
Fixed material %	69 % +/- 5
Solid in volume %	42 % +/- 5
Performance	10 to 12 m <sup>2</sup> /Kg. per coat depending of the state of the surface
Minimum recommended thickness	19-23 microns per coat
Dry-to-touch time	40 - 60 minutes
Total treat	21 days
Repainting	4 - 6 hours recommended; maximum without limit
Diluent	Water, so it is considered a fireproof paint
Presentation	Containers in 5 and 23 Kg.
Conservation	Keep away from extreme temperatures
VOC	Cat A/a (legal limit 30 g/l) max. cont. 25 g/l

**Application**

Brush, paint roller or airless spray gun. The surfaces must be clean and dry. Don't apply under temperatures below 5°C or higher than 35°C.

It's recommended to dilute to a first hand between 15-20% and for second hand a maximum 10-12%.

**Composition**

Water, emulsions, dioxide of titanium, calcium carbonate and other materials chosen for this product.

**PAINT TESTED BY GEOCISA LABORATORIES**

**Suitable for use domestic, not suitable for children.**

**Cautions**

- S2 Keep out of the reach of children  
 S23/24/25 Do not breathe vapours and avoid contact with eyes and skin.  
 S51 Use only in well-ventilated areas.

*According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.*



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**www.delapenia.com**

Factory and offices



Ctra. Orgaz, s/n  
 Apdo. 25  
 45400 Mora ( Toledo )

t: +34 925 300 409  
 f: +34 925 341 082  
 e: info@delapenia.com





**pinturas de la peña**  
fábrica de pinturas

# MONOPLAYER MATT ACRYLIC PAINT 5000-P

High Performance and Durability Acrylic Paint

Page 2 de 2



Distribuidor Oficial de:

**FESTOOL**

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

**Factory and offices**



Trofeo  
CC100  
Compromiso  
a la Calidad

*Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )*

*t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)*

Master  
Internacional  
de Empresas

