



pinturas de la peña  
fábrica de pinturas

## TRAFFIC WATER ENAMEL

Water Painting for Road Marking

Page 1 de 2

Paints for road marking, with acrylic resins in aqueous dispersion applicable in thick and very fast drying. Essentially suitable for marking of: roads, streets, car parks, etc.

### Property

Faster dry; no mess by the asphalt; very good adhesion on asphalt and concrete pavements; weatherproof; high hardness; good resistance to abrasion and impact. Reflecting effect is achieved with the addition of glass beads.

### Features



Color	White, yellow, red and blue
Finishing	Semimatt
Specific weight	1'50 - 1'60 gr. / cc.
Viscosity on having trippled	95 K.U. to 20 °C
Fixed material	65 - 63% according the colour
Performance	3'5 m <sup>2</sup> / Lt to 200 wet microns
Drying time	No pick up 20 - 30 minutes to 20°C
Stepable	21 hours
Walkable	48 hours
Repainting	12 hours
Total treat	7 - 8 days
Presentation	750ml and 3'5 Lt. containers
Type of vehicle	Water base acrylic resins

### General recommendations of application

- Shake the product until its perfect homogenization.
  - Surfaces must be clean, off dust, nitrate, etc. If it was painted above, take care that the previous paint is in good condition and well attached.
  - Can be given by brush, roller or spray.
  - Dilution: WATER
    - Spray gun "airless": 0 - 5% maximum.
    - Airbrush gun: 0 - 10% maximum.
    - Roller: Not to dilute
  - Always apply above 7°C of ambient temperature and the pavement below 40°C and 80% RH.
- Cleaning of the tools with water, immediately after use it.  
Keep away from high temperatures and frost.  
Close it after use it.

**Suitable for use domestic, not suitable for children.**

### Cautions

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

**VOC'S: Limit value of EU for the product Cat (A/i): 140 g/l (2010). Maximum content in the product 100 g/l**

*According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.*



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

[www.delapenia.com](http://www.delapenia.com)

Factory and offices



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)



Master  
Internacional  
de Empresas



**pinturas de la peña**  
fábrica de pinturas

# TRAFFIC WATER ENAMEL

Water Painting for Road Marking

Page 2 de 2



Distribuidor Oficial de:

**FESTOOL**

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

**Factory and offices**



Trofeo  
CC100  
Compromiso  
a la Calidad

*Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )*

*t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)*

Master  
Internacional  
de Empresas

