



pinturas de la peña
fábrica de pinturas

WATERBORNE ENAMEL

Waterborne Matt-Gloss-Satin Enamel

Page 1 de 3

Waterborne enamel of high quality. With great weather resistance, great whiteness, excellent opacity (coverage), good flexibility, high hardness and glossy finish. Easy to apply, of fast drying, non-yellowing, washable and with very low odour.

Suitable for the decoration of walls and ceilings; external and internal woodwork (doors, windows, gates, railings), and all kinds of wood, plaster and iron supports, etc.

It is formulated and tested in order to admit pigmentation by tintometric tinting systems; the pigmentation results in obtaining an infinity of pastel colors.

Painting tested for fire reaction by the AFITI laboratories for Euro classification according to **UNE-EN 13501-1 + A1:2010**. It obtained the best possible classification for any painting, **B,s1-d0**, for its zero contribution to fire and smoke production.



Features

Color	White
Finishing	Matt-Gloss-Satin
Specific weight	1,22 gr./cc.
Viscosity at time of packaging	95 K.U. to 25° C
Brightness at 60°	> 70 U.B.
Brightness at 20°	> 40 U.B.
Fixed matter %	50% +/- 2
Coverage	12 - 14 m ² /L per coat
Wet film recommended thickness	65 - 75 microns per coat
Dry film recommended thickness	30 microns per coat
Dry-to-touch time	40 - 60 minutes
Curing time	21 days
Recoat	6 - 8 hours
Thin with	Clean water (5 - 10% maximum)
Presentation	750 ml and 4 l cans
Conservation	Keep away from extreme temperatures
VOC	Cat A/b (legal limit 100 g/L). Max. cont. 10 g/L

Application

It can be applied on any building material, like plaster, cement, plaster, wood, iron, etc. It can be applied by brush, roller or spray. Surfaces to be painted must be clean, dry and free of dust or poorly adherent materials. Do not apply when air and surface temperatures are below 5° C or above 35° C.

Not-Painted or New Surfaces:

- Building materials:
Seal the walls with PEÑAFIJ thinned 4:1 in order to provide a homogeneous application.
In case of efflorescences or saltpeter, use a solution of thinned acid (SALFUMANT) (except in plaster), rinse with plenty of water and allow to dry. Apply a coat of PEÑAFIJ thinned 4:1.
- Iron and steel surfaces: previously protected with ANTI-CORROSION PRIMER.
- Galvanized and aluminium: Apply a first coat of PEÑAIMP.
- Wood and chipboard: Apply a coat of SYNTHETIC SEALER. Softly sand and remove the dust.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

WATERBORNE ENAMEL

Waterborne Matt-Gloss-Satin Enamel

Page 2 de 3

Surfaces already painted

- IN GOOD CONDITION:
Softly sand the surface, remove the dust and apply just like for new surfaces.
- IN BAD CONDITION:
Remove completely the painting, prepare the surface and apply as if it were a new surface.

For domestic use only. Keep out of reach of children.

Cautions

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

EUH208 Contains 2-octyl-2H-isothiazon-3-one.

Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Distribuidor Oficial de:

FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas





pinturas de la peña
fábrica de pinturas

WATERBORNE ENAMEL

Waterborne Matt-Gloss-Satin Enamel

Page 3 de 3



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas

