



# VENETIAN STUCCO

High-decoration painting with marble effect finish

Page 1 of 2

pinturas de la peña  
fábrica de pinturas

The Venetian stucco of La PEÑA is a high-decoration wall cladding and easy application for interior decoration, which allows to obtain an elegant and decorative finish reminiscent of the stuccoes of the ancient Venetian palaces. Following the common methods of application (trowel and/or scraper), the product leaves an elegant finish characterized by chiaroscuro and effects that depend on the skill of the decorator.

The Venetian stucco of the PEÑA can be applied, apart from on flat surfaces, also on particular architectural elements such as cornices, columns, etc.

## Features



|                      |   |
|----------------------|---|
| Nature               | Water-based acrylic copolymers                                |
| Finish               | Satin-Glossy smooth (marble effect)                           |
| Color                | White (base for dyeing)                                       |
| Specific weight      | 1'50gr./cc.   |
| Performance          | 1'5 - 2 m <sup>2</sup> / kg (depending on the desired finish) |
| Drying time to touch | 6 - 10 hours  |
| Curing time          | 21 days   |
| Recoat               | 24 hours  |
| Diluent              | Water (packaged in use, not diluted)                          |
| Dyed                 | Peña Universal Dye and tintometric system                     |
| Presentation         | Cans of 1 and 5 kg  |
| Conservation         | Keep away from extreme temperatures                           |
| COV'S                | Cat. A/I 200 g/l (2010). Content max.: 50 g/l                 |

## Application

Product is ready for use. It is not advisable to dilute. The surface to be painted must be clean, dry and consolidated.

On shabby surfaces:

Clean all the affected areas, remove all the material that is not well adhered, wipe all the dust and all the dirt you may have. To consolidate substrate and homogenize porosity as well as over paints to tempering, tail or lime, it is advisable to apply a first layer of fixative to the PEÑAFIJ water. Then apply a coat of EXTRA matte plastic paint and once dry, finely polish the entire surface and remove any traces of sanding dust.

### Proceed to apply Venetian Stucco:

On the firm and consistent prepared surface, apply a layer of Venetian plaster of the rock (previously dyed with the chosen color), spread with a trowel or stainless steel scraper with blunt edges, leaving the surface smooth and uniform. Apply a second coat with a scraper in an asymmetrical way, leaving a space between passes of a few centimeters. Apply a third coat with a scraper between the spaces left in the previous pass, to acquire a greater contrast of tonalities.

### Finish:

If it is desired to shine: with the surface completely dry (24 hours min.), pressing with the blunt edge of the scraper or the trowel obtains shines. The scraper without stucco is dragged over the coated area several times, making the surface completely smooth and increasing its luster. If you want to obtain a higher level of brightness and protection, you can apply with a wool mitten a special wax hand for stucco DE LA PEÑA.

**Suitable for domestic use. Keep out of reach of children.**



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

[www.delapenia.com](http://www.delapenia.com)

Fábrica y oficinas



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)





## VENETIAN STUCCO

High-decoration painting with marble effect finish

Page 2 of 2

pinturas de la peña  
fábrica de pinturas

### Cautions

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.  
 EUH208 Contains 2-octyl-2H-isothiazon-3-one.  
 Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).  
 May produce an allergic reaction.

*According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.*



Distribuidor Oficial de:

**FESTOOL**

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

Fábrica y oficinas



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)

Master  
Internacional  
de Empresas

