



pinturas de la peña
fábrica de pinturas

WATER REPELLENT BASE WATER

Primer water repellent for the protection of walls

Page 1 de 2

This water repellent is used to protect any kind of surfaces with pore and no alkaline without modifying their original aspect.

It is the ideal water- repellent which does not modify the original aspect but which prevents form the damage and the dirt caused by the weather, specially the caused by the ice.

It is made by water- repellent agents which prevent from the humidity (mold, rust and saltpeter), leaving clean the supports and keeping the supports clean.

It is does not become a film so it is permeable to the steam, allowing the surface to breathe.



Characteristics

Aspect	Slightly milky liquid
Finishing	Invisible
Specific weight	1,00 gr./cc.
Performance	2 - 5 m ² / lt (depending of the surface)
Total drying time	Totally conditioned by the temperature, support and HR
Repainting	Minimum: 8 hours; Maximum: No limit
Diluent	Envasado al uso
Presentation	de 1,5 and 25 lt. containers
Conservation	Keep away from extreme temperatures

Applications

The product must not be mixed with a thinner. It can be applied with a brush, a paint roller or with a spray gun (do not use high pressures, over 3 bares), etc. Apply from bottom to top to make sure the product is applied in a uniform coat. Before its application the surface must be totally clean, without saltpeter and oil and without any materials stick on it. The surface can be a bit wet but its effectiveness is much bigger if the surface is totally dry. Over new mortars it must be left to harden totally (30 days approximately). It must be used in a uniform way to avoid the appearance of different zones as the rain; the number of coats depends on the pore of the surface. It is usually needed a coat of paint.

It must be applied with temperatures between 0°C and 35°C.

Cleaning of tools

Clean the used tools with water and soap if the product is fresh. Once it is dry, the tools must be cleaned with products

Composition

Water and polisiloxanes.

Suitable for use domestic, not suitable for children.

Cautions

S2 Keep out of reach of children
S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC),



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

WATER REPELLENT BASE WATER

Primer water repellent for the protection of walls

Page 2 de 2

not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

*Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)*

*t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com*

Master
Internacional
de Empresas

