



pinturas de la peña
fábrica de pinturas

WATER REPELLENT BASE SOLVENT

Primer water repellent for the protection of walls

Page 1 de 2

This water repellent is used to protect any kind of surfaces with pore and no alkaline without modifying their original aspect.

It is the ideal water- repellent which does not modify the original aspect but which prevents the damage and the dirt caused by the weather, specially the caused by the ice.

It is made by water- repellent agents which prevent from the humidity (mold, rust and saltpeter), leaving clean the supports and keeping the supports clean.

It is does not become a film so it is permeable to the steam, allowing the surface to breathe.



Features

Aspect	Slightly milky liquid
Finishing	Invisible
Specific weight	1,00 gr./cc.
Performance	2 - 5 m ² / lt (Depending the wall)
Total drying time	Totally conditioned for the temperature, the surface and HR
Repainting	Minimum: 8 hours; Maximum: No limit
Diluent	Container ready for the use
Packaging	1, 5 and 15 lt. containers
Conservation	Keep away from extreme temperatures

Application

Product is ready for the use, it must not be diluted, and it can be applied using any conventional method, brush, roller, spray gun, (do not use high pressure < 3 bars), etc. The surfaces to be treated must be clean of salt, fat, completely free of moisture and foreign elements (new mortars leave completely, set 30 days approximately), apply in a uniform way by all the wall to avoid the appearance of uneven areas after rain; the number of coats depends on the porosity of the facade. Normally, it is enough with two coats. It should be applied at temperatures between 0°C and 35°C

Cleaning of the tools

Cleaning can be done with turpentine, simile universal solvent, etc.

Composition

Water and polisiloxanes.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use in well ventilated locations.

SEE THE PRODUCT DATA SAFETY SHEET



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Ctra. Orgaz, s/n
 Apdo. 25
 45400 Mora (Toledo)

t: +34 925 300 409
 f: +34 925 341 082
 e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

WATER REPELLENT BASE SOLVENT

Primer water repellent for the protection of walls

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

*Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)*

*t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com*

Master
Internacional
de Empresas

