



pinturas de la peña
fábrica de pinturas

INDOOR STONE PASTE

Textured covering for interior

Page 1 of 2

The INDOOR STONE PASTE is a stone-framed sand coating with easy application to roller and high hardness finishes.



Features

Color	White and pastel colors, on request
Finish	Rough granulated
Specific weight	1,90 gr./cc.
Performance	1,5 m ² /kg., according the relief to get
Drying time to touch	8 to 10 hours, depends on environment
Diluent	Water, so it is considered fire retardant
Presentation	Bags of 24 Kg. and cans of 25 Kg.
Conservation	Keep away from extreme temperatures

Application

It can be applied with wool or foam roller and other rubber ribbed rollers, pneumatic equipment, brushes or brushes. The faces to be painted must be clean and dry, being able to be these of cement, plasters of lime-cement, gypsum, brick, polyester and foam of polyurethane, wood and natural or artificial stone indoors. When applied to plaster or absorbent surfaces, or at elevated temperatures, prime with a part of the stone paste, diluted in 30% water or PeñaFij to 4x1 in water.

Do not apply to temperatures below 5 °c or above 35 °c.

Composition

Water, emulsions, titanium dioxide, calcium carbonate, marble grain and additives adapted to the same

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of the reach of children
 S23/24/25 Do not breathe vapours and avoid contact with eyes and skin.
 S51 Use only in well-ventilated areas.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Fábrica y oficinas



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

INDOOR STONE PASTE

Textured covering for interior

Page 2 of 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Fábrica y oficinas



Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas

