



pinturas de la peña
fábrica de pinturas

PEÑA ELASTIC FIBER

Anti-leaks Elastic Coat (Rubber) reinforced with fiber glass

Page 1 de 2

Paint made with acrylic emulsions, inert glass fibers and special loads that provide you with a highly elastic, perfect to apply to terraces and other walls which the humidity is revised. This painting by its nature and by its richness in additives fungicides prevents the development of stains from the mold, mildew, algae, providing high power anti aging in wet, and may apply both indoor and outdoor rooms.

Its high content in inert glass fiber provides a high filling capacity, as well as a great structural strength.

Features

Color	White, oxide red, and terracotta. Another colors under order.
Finishing	Glossy
Specific weight	1,33 +/- 0,05 gr./cc.
Viscosity on having trippled	115 +/- 5 K.U. to 25 °C
Fixed material	65 % +/- 1
Performance	1 - 2 m ² /Kg (Minimum consumption recommended in 3 cross hands .)
Drying time at touch	30 - 60 minutes
Treat	21 days
Repainting	It is recommended the course of 12 to 14 hours a minimum between the different hands of the application.
Diluent	Water, so it is considered fireproof.
Presentation	5 and 18 Kg. containers
Conservation	Keep away from extreme temperatures



Application

PEÑA ELASTIC paint, can be applied by brush or roller, apply thin layers and dry before applying a second coat, as well, to get a film thickness of the thickness desired, since it does not crack or break. The walls where it should be applied must be clean and free of residue of old paint, it should not be applied at temperatures below 5°C or above 30°C (both in environments and support), or if are expected frost or rain immediate application (6-12 hours), avoid humid environments. Supplied to use. The application of three hands of the product to obtain satisfactory results is provided for its application.

We do not recommend a dilution of product, to not get side effects of reduction of solid content and to avoid problems in the application, and must apply to the viscosity of shipping. Cleaning utensils must be with water.

Composition

Water, acrylic emulsions, fillers, pigments of high quality and specially selected additives.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

PEÑA ELASTIC FIBER

Anti-leaks Elastic Coat (Rubber) reinforced with fiber glass

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas

