



pinturas de la peña
fábrica de pinturas

PEÑA ELASTIC COLOURLESS

Transparent Waterproof Elastic Coat (Rubber)

Page 1 de 2

Paint made from acrylic elastic emulsions that provide a high flexibility, perfect for applying on terraces and other walls in which the moisture is rerouted. This painting by its nature and its richness in fungicide is anti-mildew, anti-fungal and anti-algae, giving an anti-ageing power in humid spaces, being able to be applied both indoors and outdoors.

Characteristics



Color	Colorless
Finishing	Glossy
Specific weight	1,05 +/- 0,05 gr./cc.
Viscosity on having trippled	90 +/- 5 K.U. to 25 °C
Fixed material	40 % +/- 1
Performance	1 - 2 m ² /Kg (Minimum consumption recommended in 3 cross hands .)
Drying time at touch	30 - 60 minutes
Treat	21 days
Repainting	It is recommended the course of 12 to 14 hours a minimum between the different hands of the application.
Diluent	Water, so it is considered fireproof.
Presentation	1, 4 and 16 Kg. containers
Conservation	Keep away from extreme temperatures.

Application

PEÑA ELASTIC paint, can be applied with brush or roller, apply thin layers and dry before applying a second coat, as well, to get a film thickness of the thickness desired, since it does not crack or break. The walls where is to be applied must be clean and free of residue of old paint, it should not be applied at temperatures below 5°C or above 30°C (both in environments and support), or if are expected frost or rain immediate application (6-12 hours), avoid humid environments. Supplied to use for your application the application of three coats of the product being essential for satisfactory results.

We do not recommend a dilution of product, to not get side effects of reduction of solid content and to avoid problems in the application, and must apply to the viscosity of shipping. Cleaning utensils should be done with water.

Composition

Water, acrylic emulsions, fillers, pigments of high quality and specially selected additives.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

PEÑA ELASTIC COLOURLESS

Transparent Waterproof Elastic Coat (Rubber)

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



**Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)**

**t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com**

**Master
Internacional
de Empresas**

