



pinturas de la peña
fábrica de pinturas

PEÑA-FIJ

Fixative for poorly adhered limes and walls

Page 1 of 1

Pure acrylic dispersion in aqueous medium, fine particle with excellent penetrability and adhesion on porous supports, resistant to the alkalinity of the support as cement mortars, concrete, brick... Water vapour Permeable, allowing the perspiration of the support, regulates the absorption in old or shabby walls, increasing the adhesion of the posterior layers of the finishing paint. Diluted in proportion 1 to 4 does not create film, can be used both indoor and outdoor.



Features

Color	Milky white (wet); Colorless (dry)
Finish	Semimate to gloss depending on the dilution and layers
Specific weight	1.05+/- 0.03 gr./cc.
Viscosity at time of packaging	< 40 K.U.
Fixedmatter	24% +/- 2
Performance	8- 10 m ² /lt. Depending on the porosity of the surface
Drying time	40- 60 minutes to touch
Recoat	Minimum 2 hours, maximum: unlimited
Diluent	Clean water (Up to 1 to 4 peñafij-water)
Presentation	Cans of 1, 5 and 25 Lt.
Conservation	Keep away from extreme temperatures

Application

The surfaces to be painted must be clean and dry, free of dust, grease, saltpeter, etc. It can be applied on any construction material, plaster, cement, etc. Its application can be by brush, roller or sprayed. Depending on the work to be done it is recommended to dilute: 1 (PEÑAFIJ) 1-1 ½ (water) to leave as varnish; 1 (PEÑAFIJ) 4 (water) to use as a consolidator without leaving coat. It should not be applied at temperatures below 5 °c or above 35 ° C. Nor relative humidity above 80%

Composition

Water, pure acrylic emulsions, and specific additives.

Suitable for domestic use. Keep out of reach of children.

Cautions

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Fábrica y oficinas



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

