

Plastic paint coating specially formulated for the decoration and protection of new and old facades, with a high covering power and excellent mechanical and esthetic qualities.

It is a coating formulated with pure acrylic emulsions that confer excellent behavior on any surface and high durability to both quartering and yellowing, has a high permeability to water vapor (allows transpiration to the surface) and presents a high impermeability to the liquid water by its content in hydrofugal additives.

Features



Color	White
Finish	Matt
Specific wight	1,66 +/-0,05 gr./cc.
Viscosity	110 K.U. a 25 °C
Fixed matter	69%
Performance	8 - 10 m ² /Kg
Drying time	1-2 hours
Curing	21 days
Recoat	6-8 hours minimum
Diluent	Water (maximum 25% in weight)
Presentation	Cans of 23 Kg.
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a (legal limit 30g/l) content max 25 g/l

Application

It is a product also indicated in exteriors as indoors, it can be applied on cement, plaster, concrete, brick, stone, etc. Its application can be brushed, roller or sprayed. The walls to be painted must be clean and dry and should not be applied to temperatures below 5 °C or above 35 °C.

Composition

Water, pure acrylic emulsion, calcium carbonates and other special additives chosen for this product.

Suitable for domestic use. Keep out of reach of children.

Cautions

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

EUH208 Contains 2-octyl-2H-isothiazon-3-one.

Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl.2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

May produce an allergic reaction.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas



pinturas de la peña
fábrica de pinturas

SPECIAL CLADDING FACADES

High Performance Acrylic Coating

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

*Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)*

*t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com*

Master
Internacional
de Empresas

