



pinturas de la peña  
fábrica de pinturas

## PEÑA ELASTIC

Anti-leaks Elastic Coat (Rubber)

Page 1 de 3

Paint made with acrylic emulsions and special loads that provide a highly elastic, perfect for applying to terraces and other walls through which moisture passes. This painting by its nature and by its richness in additives fungicides prevents the development of stains from the mold, mildew, algae, providing high power anti aging in wet, and may apply both interior and exterior rooms.

### Features

Color	White, oxide red, terracotta, green, black, brown and grey. Another colours to order.
Finishing	Satin
Specific weight	1,33 +/-0,05 gr./cc.
Viscosity at time of packaging	120 +/- 5 K.U. to 25 °C
Fixed material %	62 % +/- 5
Solid on volume %	47% +/- 5
Performance	1 - 2 m <sup>2</sup> /Kg ( Minimum consumption recommended in 3 cross coats).
Minimum dry thickness	57-61 microns per coat (174-179 total microns)
Drying time at touch	30 - 60 minutes
Total treat	21 days
Repainting	It is recommended 12 to 14 hours a minimum between the different coats of the application, maximum without limit.
Diluent	Fresh water
Presentation	1 Kg., 5 Kg. and 18 Kg. containers
Conservation	Keep away from extreme temperatures.
COV'S	Cat A/a (legal limit 140 g/l) max. cont. 40 g/l
Temp. of application	5°C - 30°C
Relative humidity	Lower than 80%



### Application

PEÑA ELASTIC paint can be applied to the brush or roller, apply thin layers and dry before applying a second coat, as well, to get a film thickness of the thickness desired, since it does not crack or break. The walls where it is going to be applied must be clean and free of residues of old painting , it should not be applied at temperatures below 5°C or above 30°C (both in environments and support), or if are expected frost or rain, immediate application (6-12 hours), the humidity should be less than 80%. The temperature of the substrate must be 2-3°C above the dew point to prevent condensation. The first coat can be diluted with 10-15% water, rest of coats 5-10% as maximum, being essential minimum three cross coats of product application to obtain satisfactory results. (dilution must take into account for the calculation of the humid thickness). Cleaning utensils must be with water.

### Composition

Water, acrylic flexible and elastic emulsions, fillers, pigments of high quality and specially selected additives.

**Suitable for use domestic, not suitable for children.**



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

[www.delapenia.com](http://www.delapenia.com)

Factory and offices



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)





pinturas de la peña  
fábrica de pinturas

## PEÑA ELASTIC

Anti-leaks Elastic Coat (Rubber)

Page 2 de 3

### Cautions

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P501 Dispose of the contents/containers in accordance with the current legislation on waste treatment.

EUH208 Contains 2-octyl-2H-isothiazon-3-one.

Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl.2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

May produce an allergic reaction.

*According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.*



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

**Factory and offices**



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)



Master  
Internacional  
de Empresas



pinturas de la peña  
fábrica de pinturas

# PEÑA ELASTIC

Anti-leaks Elastic Coat (Rubber)

Page 3 de 3



Distribuidor Oficial de:

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

**Factory and offices**



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)

Master  
Internacional  
de Empresas

