



pinturas de la peña
fábrica de pinturas

WATERBORNE POLYURETHANE VARNISH

Waterborne Polyurethane Varnish for Passable Floors

Page 1 de 2

Polyurethane varnish base water with high performance and specially designed for a long-lasting protection of mineral floorings. It can be used directly (1 component) or catalyzed (2 components) if you want a higher chemical and mechanical resistance.

It has high resistance to stains, highly resistant to chemical attack, and high abrasion resistance. Easy and fast to apply. It can be used for the protection of all types of flooring, indoors and outdoors. It gives long-lasting protection creating a highly abrasion-resistant protective layer reducing dirt and pavement maintenance times.

Features

BASE (COMP. A)	
Color	Colorless, Transparent
Finishing	Brightness
Specific weight	1,05 +/-0,03 gr./cc.
Solid in volume	31 % +/- 1
Viscosity at time of packaging	80 K.U. to 25 °C
Performance	8 - 10 m ² /Kg. coat depending on the state of the walls
Life of mix	120 Minutes
Walkable	24 hours
Pissable	48 hours
Treat	7 - 8 days
Repainting	12 hours
Diluent and clean of tools	Water
Packaging	4 and 14 Lt containers
Conservation	Keep away from extreme temperatures
HARDENER (COMP. B)	
Colour	Colorless, Transparent
Specific weight	1,10 +/-0,05 gr./cc.

Application

It can be applied by brush or short hair roller. Walls must be clean, dry, and well consolidated. Do not apply to stands under 10°C over 30°C, and the air humidity should be less than 80%.

If you want the highest chemical and mechanical resistance the catalyzed form will be used:

Add hardener (Comp. B) to the base (Comp. A), mixing them by hand or with mechanical stirrer of low rpm (so as not to produce foam) until you get a perfect homogenization. Wait 3 to 5 minutes approximately before you begin your application.

When it's mixed, the product is ready to be used, do not dilute (at most 5% water). The application of two crossed hands is recommended. After 24 hours it is passable with caution, maximum hardness reaches approximately 7 days.

Suitable for domestic use, not suitable for children.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas

De la Peña

WATERBORNE POLYURETHANE VARNISH

Waterborne Polyurethane Varnish for Passable Floors

Page 2 de 2

pinturas de la peña
fábrica de pinturas**Cautions**

- S2 Keep out of reach of children
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com
Factory and officesTrofeo
CC100
Compromiso
a la CalidadCtra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.comMaster
Internacional
de Empresas